




DIMENSIONS:

23.75"(L) x 23.75"(H) x 1.71"(D)



Emergency System
Pre-installed (In 2X2 Installed
but not attached to fixture)



23.75" x 23.75" x 1.71"

LP-2X2-40W-50K-DS-EM
LP-2X2-40W-40K-DS-EM

**LED PANEL LIGHTS WITH EMERGENCY
BATTERY BACKUP**

Ideal for hotel, offices, retail outlets, restaurant, parking garages, storage room, conference room, education facilities and more.

ELECTRICAL SPECIFICATIONS:

- Voltage: 100-277VAC, 50/60Hz
- Wattage: 40W
- Current: 1050mA
- Power factor: >0.90
- Efficacy: 110LM/W
- THD: <15%

HOUSING SPECIFICATIONS:

- External driver mounted on top
- Earthquake hooks and suspension hooks pre-installed
- Operating temperature: -68°F ~ 104°F
- Lifespan: 50,000 Hrs.

CERTIFICATIONS: FC, UL, DLC



MODEL	WATTS	VOLTAGE	LUMENS	COLOR TEMP
LP-2X2-40W-50K-DS-EM	40W	100~277VAC	4400LM	5000K
LP-2X2-40W-40K-DS-EM	40W	100~277VAC	4400LM	4000K

LIGHTING SPECIFICATIONS:

- Dimming: 0~10V dimmable
- LED type: 4014SMD LM80
- No. of LED: 216
- Total lumens: 4400LM
- Color temperature: 5000K/4000K
- Color rendering index: >80
- Soft and wide light emitting
- No infrared rays, no ultraviolet radiation, no thermal effect
- No flickering, no humming, no RF interference

EMERGENCY UNIT SPECS :

- Input voltage: 100~277VAC, Output power: 20W (Max), Emergency operation: ≥90 mins., Recharge: 24 Hrs.
- Pre-installed but not attached to fixture

WARRANTY: 5 years

