

ULR-IP54-HO

DAMP

HIGH OUTPUT



TECHNICAL SPECIFICATIONS:

- :: LED: SMD2835 chip spaced 5/8" on center, 19 LED per foot, 0.24 watts each chip
- :: Dimmable using a magnetic driver
- :: Cutting increment: Every 4 inches
- :: Working voltage: 24V DC (LED driver required)
- :: Power: 4.4 watts per foot
- :: Lumens: 350 lumens per foot, 18.5 LM per LED
- :: CRI: 90
- :: Max run: 20'
- :: 120° beam angle
- :: 3M double sided tape is preinstalled
- :: Includes 1 female ribbon-to-power supply connector (Prewired) and 1 male plug for connection to next ribbon (Prewired)
- :: Operating temperature: -4°F - 104°F
- :: IP54
- :: 5-year warranty

Application:

- :: Ideal for undercabinet, soffit, display cases and toe kick lighting.



**16.4FT
ROLLS**

24V DAMP LOCATION HIGH OUTPUT LED RIBBON

CATALOG NO.	COLOR TEMP	WATTS PER FT.	REEL LENGTH	LUMENS PER FT.	LEDs PER FT.	WIDTH	LED TYPE	MAX RUN
ULR-IP54-16F-HO-50K	5000K	4.4	16.4 ft.	350	19	0.4 in.	SMD2835	20 ft.
ULR-IP54-16F-HO-40K	4000K	4.4	16.4 ft.	330	19	0.4 in.	SMD2835	20 ft.
ULR-IP54-16F-HO-30K	3000K	4.4	16.4 ft.	310	19	0.4 in.	SMD2835	20 ft.
ULR-IP54-16F-HO-27K	2700K	4.4	16.4 ft.	310	19	0.4 in.	SMD2835	20 ft.

TANDEM COUPLINGS & POWER FEED CABLES

CATALOG NO.	DESCRIPTION	LENGTH
ULR-IP54-HO-COUP-6I-WR	Coupling to connect 2 high output ribbons	6"
ULR-IP54-HO-COUP-3F-WR	Coupling to connect 2 high output ribbons	3'
ULR-IP54-HO-COUP-NO-WR	Coupling to connect 2 high output ribbons	No wire
ULR-IP54-HO-CONN-6I-WR	Power feed cable, 1side ribbon connector, 1 side female socket to driver	6"
ULR-IP54-HO-CONN-3F-WR	Power feed cable, 1side ribbon connector, 1 side female socket to driver	3'
ULR-IP54-HO-CONN-3F-PT	Power feed cable, 1side ribbon connector, 1 side open end	3'
ULR-IP54-HO-CONN-10F-PT	Power feed cable, 1side ribbon connector, 1 side open end	10'

G6